

- Simplified installation.
- Frontal door for easy operation and maintenance.
- Steel body, good against vandalism.
- Five different connection types selectable without restrictions in each of the two connections.
- RGB light indicator of charge status on each connection.
- DLM 2.0 included. (Load management internally between both connections and also externally with other FUSION or RAPID chargers).
- Ethernet and WiFi by default. 3G modem optional.
- Ethernet switch to reduce the cost of Ethernet wiring. (less longitude and external switch is not necessary)
- OCPP 1.5 / 1.6
- MID certified meters
- Color TFT 4.3" improving user interface.
- Different authentication methods: Local (RFID card), Remote (OCPP), without authentication (plug & charge).
- Accessibility for the disabled has also been considered, complying with international standards regarding the height of connectors/ display that facilitates its operation.
- Overvoltage protections by default (Type III)
- Blackout warning message



Single Phase		Retail
FW1MW-N2N2	Type 2 (7,4 kW) + Type 2 (7,4 kW) - MID - RCD & MCB	
FW1MW-N3N3-DD	Type3A (3,7 kW) + Type3A (3,7 kW) - MID - RCD & MCB - DC leakage current detector	
FW1MW-S2N3-DD	Type2 shutters (7,4 kW) + Type3A (3,7 kW) - MID - RCD & MCB - DC leakage current detector	
FW1MW-S2S2-DD	Type2 shutters (7,4 kW) + Type2 shutters (7,4 kW) - MID - RCD & MCB - DC leakage current detector	
FW1MW-S2C2-DD	Type2 shutters (7,4 kW) + Cable Type2 (7,4 kW) - MID - RCD & MCB - DC leakage current detector	
FW1MW-C1C1-DD	Cable Type1 (7,4 kW) + Cable Type1 (7,4 kW) - MID - RCD & MCB - DC leakage current detector	
FW1MW-C2C2-DD	Cable Type2 (7,4 kW) + Cable Type2 (7,4 kW) - MID - RCD & MCB - DC leakage current detector	
Three Phase		Retail
FW3MW-N2N2	Type 2 (22 kW) + Type 2 (22 kW) - MID - RCD & MCB	
FW3MW-S2N3-DD	Type2 shutters (22 kW) + Type3A (3,7 kW) - MID - RCD & MCB - DC leakage current detector	
FW3MW-S2S2-DD	Type2 shutters (22 kW) + Type2 shutters (22 kW) - MID - RCD & MCB - DC leakage current detector	
FW3MW-S2C2-DD	Type2 shutters (22 kW) + Cable Type2 (22 kW) - MID - RCD & MCB - DC leakage current detector	
FW3MW-C2C2-DD	Cable Type2 (22 kW) + Cable Type2 (22 kW) - MID - RCD & MCB - DC leakage current detector	
Protections		Retail
DD	DC Leaks - Direct current 6mA leak detector, equivalent to Type B RCD	
AUTO 2P*	RCD autoreset for single phase charger	
AUTO 4P*	RCD autoreset for three phase charger	
* not available for Fusion Wall with C2C2 cables		
Communication		Retail
3G	3G modem for Fusion	
Other Options		Retail
Plug	Different plugs	on request
Warranty	Warranty extension	on request

VAT excluded prices

EXWORKS prices (Transport included for direct shipment from Spain, minimum 1 pallet - 6 chargers)

2 years warranty